

The ACD2 is the most recent addition to ASP's Accu-DrainProduct Line. Thisnew electric noloss drain was designed to provide the same reliability as our current ACDs but in a smaller footprint. It still has ASP'ssignature translucent vessel for a fast and simple operational check, a robust non-clogging Posi-Valve that eliminates the need for additional strainers, and for it's size has a large discharge capacity of 1.5 oz.

The ACD2 is ASP's first no loss electric drain that is light enough to be suspended from prefilters, after-filters, or other system equipment. It is also ideal for applications where there is limited space in the system for the drain. This drain rounds out our Electric Zero Loss drain offerings so customers can use our dependable drains on all different size systems and types of equipment .



Making the World Safer, Healthier and More Productive

Filtration Group Corporation

As Part of Filtration Group, Air System Products is a leader in condensate management in the air and gas compressor industry, offering drains and oil/water separators in all manufacturing markets. We lead the industry in reliability, service and support, while offering an industry standard 2 Year Warranty on our complete Robo-Drain line.

All ASP products are manufactured right here in the USA, so you know that you are getting a product that is built to last. From our 'bullet proof' Robo-Drain line of condensate drains, to our worry free 24-Hour continuous run Accu-Sep OWS System, you can rest assured that the same attention to detail is taken in all our products as you would put into your own.





51 Beach Ave, Lancaster, NY 14086 716/683.0435 www.airsyspro.com



Explore The Complete Accu-Drain Line



Small Lightweight Zero-Loss Drain

Zero-Loss Drain with Internal Posi-Valve

SPECIFICATIONS		
Inlets	(1) 1/2" NPT	
Outlets	1/4" NPT	
Comp. Capacity	500 CFM	
Dryer Capacity	1000 CFM	
Filter Capacity	3000 CFM	
Pressure	0 - 200 PSI	
Operating Temp.	32° - 180° F	
Weight	2.6 lbs.	
Discharge	1.5 oz. per cycle	
Voltage	115v - 8' Power Cord	

MATERIALS		
Reservoir	Aluminum & Composite	
Valve	Aluminum & Stainless Steel	
Float	Stainless Steel	



Energy Efficient Zero-Loss Drain
Electric Automatic Condensate Drain

SPECIFICATIONS	
Inlets	(2) 1/2" NPT
Outlets	1/4" NPT
Comp. Capacity	1000 CFM
Dryer Capacity	2000 CFM
Filter Capacity	4000 CFM
Pressure	0 - 200 PSI
Operating Temp.	32° - 180° F
Weight	5 lbs.
Discharge	8 oz. per cycle
Voltage	115v - 8' Power Cord
Options & Accesories	BSPP Fittings, Alarm

MATERIALS		
Reservoir	Aluminum & Composite	
Valve	Brass	
Float	Stainless Steel	



Higher Volume Energy Efficient Zero-Loss Drain Electric Automatic Condensate Drain

SPECIFICATIONS		
Inlets	(2) 1/2" NPT	
Outlets	1/4" NPT	
Comp. Capacity	2000 CFM	
Dryer Capacity	4000 CFM	
Filter Capacity	12,000 CFM	
Pressure	0 - 200 PSI	
Operating Temp.	32° - 180° F	
Weight	10 lbs.	
Discharge	21 oz. per cycle	
Voltage	115v - 8' Power Cord	
Options & Accesories	BSPP Fittings, Alarm	

MATERIALS		
Reservoir	Aluminum & Composite	
Valve	Brass	
Float	Stainless Steel	